
FLOOR DRAINS

-44 Option, Fixed Extension Collar




ORDERING INFORMATION

To specify or order a fixed extension collar with floor drain, add Option (-44) and height required to type number of drain.

Example: Type 32103 with a 6" extension would be designated: Type 32103 (-44)-6".

SERIES NO.	B In.	D ln.	E Min.
32100, 32150, 32160	9-1/8	8-1/8	2
32200, 32300	12-5/8	11-3/4	2


(-AE) Option, LEVELEZE® Adjustable Extension




(-AE) OPTION, LEVELEZE® ADJUSTABLE EXTENSION

The adjustable integral top is mated to the body and support ring with a heavy machined thread which permits virtually unlimited top level adjustment to accommodate various deck thicknesses. The line contact between the threads provides positive circumferential support of the top at any adjusted elevation.


(-J) Backwater Valve



A Series Round Strainer shown with Optional (-J) Backwater Valve Formerly AJ Series Strainer



E Series Round Tractor Strainer shown with Optional (-J) Backwater Valve Formerly EJ Series Strainer



S Series Square Strainer shown with Optional (-J) Backwater Valve Formerly SJ Series Strainer

(-J) OPTION, BACKWATER VALVE

For use in any Josam adjustable strainer in areas subject to back flow conditions with the exception of Series C and M. Cannot be used in conjunction with (-80) Option, Perforated Stainless Steel Basket.

Outlet Connections

JOSAM drains are furnished with outlets for connection to most types of pipe. The timesaving, economical JIFFEE-JOINT Gasket is used for inside caulk connections (-X) to extra heavy or service weight soil pipe. No-hub spigot outlets (-Z) are also available for connection to no-hub soil pipe. The JIFFEE-SET Outlet (-Y) is for connecting hub outlet drains to PVC and ABS, service weight or no-hub soil pipe. Threaded outlets (-T) can be obtained on many series.

