SANITARY FLOOR SINKS

SUPER-FLO-SEPTOR® Features

Now, more than ever before, facilities such as hospitals, laboratories and areas where foods are processed and handled, are objectively evaluated for optimum environmental sanitation. Recognizing this requirement, JOSAM developed the SUPER-FLO-SEPTOR® line of Sanitary Floor Sinks.

SUPER-FLO® GRATE AND SANITARY SLOPING RIM

DOUBLE DRAINAGE OR ANCHORING FLANGE

When this flange is provided, weepholes are automatically furnished to assure the drainage of any secondary moisture which may be present. The additional option of a flashing clamp device assures the positive bonding of the flashing between the double drainage flange and clamp ring.

This unique combination insures that the rim portion and side walls of the drain will be washed clean with any flow of liquid.

ACID-RESISTING INTERIOR

The acid-resisting interior, furnished standard on all SUPER-FLO-SEPTORS®, provides the smooth surface necessary for sanitation and protection from corrosion in food processing applications.



Sanitation is promoted by the smooth, uniformly contoured interior which has no corners or crevices to escape the cleansing action of drainage flow. Available in depths of 6, 8 and 10 inches (depending on series) to suit every application.

INTERNAL DOME

SUPER-FLO-SEPTORS® have an internal dome which acts as a secondary strainer to intercept debris which could cause blockage of drain lines. The dome is easily removed to facilitate cleaning.

Outlet Connections

JOSAM SUPER-FLO-SEPTORS® are furnished with outlets for connection to extra-heavy, service weight or no-hub pipe. The timesaving, economical JIFFEE-JOINT is used for inside caulk connections. For outlet type, specify (-X) for inside caulk outlet and (-Z) for no-hub spigot outlet.



