

# MEADRAIN® Supreme



## U1000

Clear Width: 4" interior

Total Width: 6"

Fall Options: Available with built in fall, neutral or stepped fall

Locking System: STANDARD lock bar system

Edge Protection: Without metal edge protection

Load Class: A, B, C, E\*\*



Channel units with linear fall

product description	length [inches]	total height [inches]		product #	lbs/ unit
		start	end		
U1001	39.4	5.9	6.1	151005	32.4
U1002	39.4	6.1	6.3	151007	33.3
U1003	39.4	6.3	6.5	151009	34.2
U1004	39.4	6.5	6.7	151011	35.3
U1005*	39.4	6.7	6.9	151013	35.9
U1006	39.4	6.9	7.1	151019	36.6
U1007	39.4	7.1	7.3	151021	37.7
U1008	39.4	7.3	7.5	151023	38.8
U1009	39.4	7.5	7.7	151025	39.7
U1010*	39.4	7.7	7.9	151027	40.6
U1011	39.4	7.9	8.1	151033	41.7
U1012	39.4	8.1	8.3	151035	42.6
U1013	39.4	8.3	8.5	151037	43.4
U1014	39.4	8.5	8.7	151039	44.3
U1015*	39.4	8.7	8.9	151041	45.5
U1016	39.4	8.9	9.1	151047	46.3
U1017	39.4	9.1	9.2	151049	47.2
U1018	39.4	9.2	9.5	151051	48.1
U1019	39.4	9.5	9.7	151053	49.2
U1020*	39.4	9.7	9.8	151055	50.3

\* With connection facility for vertical discharge outlet connector Ø 4" or silt box/gully

### Note

On request channel elements with total height of 9.9 inches to 12.0 inches are available. (U1021-U1030)

**Lock Bar System:** Locking bar with stainless steel hardware designed to secure grate into preformed areas.

\*\*Utilize DI1000 rail to achieve E load class rating with appropriate grate

### Applications

#### Sidewalks, Shopping Areas

- Polymer concrete edge to match surrounding concrete deck
- Select galvanized slotted grate for economical versatile top

#### Auto Dealership, Warehouse Truck Bays

- Efficient drainage for low flow area
- Select DI1000 ductile iron rail and grating for areas exposed to forklift traffic