

MEADRAIN® Supreme



J1000

Clear Width: 4" interior

Total Width: 5.1"

Edge protection: Integrated galvanized steel protected edge

Fall Options: Available with built in fall, neutral or stepped fall

Locking System: CLIPFIX locking recess or STANDARD

Outlet: 4" bottom or end outlet connection

Load Class: A, B, C, E

Channel units without fall

product description	length [inches]	total height [inches]	product #	lbs/unit
J1000.0 ¹⁾	39.4	5.9	155401	29.8
J1000.1 ¹⁾²⁾	19.7	5.9	155403	15.4
J1005.0 ¹⁾	39.4	6.9	155415	34.2
J1005.1 ¹⁾²⁾	19.7	6.9	155417	18.7
J1010.0 ¹⁾	39.4	7.9	155429	37.9
J1010.1 ¹⁾²⁾	19.7	7.9	155431	22.0
J1015.0 ¹⁾	39.4	8.9	155443	42.8
J1015.1 ¹⁾²⁾	19.7	8.9	155445	25.3
J1020.0 ¹⁾	39.4	9.8	155457	47.8
J1020.1 ¹⁾²⁾	19.7	9.8	155459	27.6

¹⁾ With connection facility for vertical discharge outlet connector Ø 4" or silt box/gully

²⁾ Connecting facility for corner and cross junction



Channel units for stepped fall

As connecting elements for stepped fall (with 2.5% fall)

product description	length [inches]	total height [inches]		product #	lbs/unit
		start	end		
J1000-5	39.4	5.9	6.9	155461	32.2
J1005-10	39.4	6.9	7.9	155463	35.9
J1010-15	39.4	7.9	8.9	155465	39.9
J1015-20	39.4	8.9	9.8	155467	45.5

Note

For installation of stepped fall with neutral channels J1000.0 and J1005.0 connect with J1000-5.

CLIPFIX: Recesses in channel edge accepts grate with pre-attached lock device to ensure positive locking of grate to channel. Removal of grate provides an unobstructed channel cross section for simple cleaning. Available on J1000 and S1000.

Applications

Public Areas

- Galvanized protected edge provides clean, uniform edge to finish surface
- Select heel-proof perforated or slotted grates

Warehouse facilities

- Protected edge prevents chipping abuse from forklift wheels
- Select ductile iron or reinforced slotted grates to withstand heavy loads