

MEADRAIN® Supreme



J1000

Clear Width: 4" interior

Total Width: 5.1"

Edge protection: Integrated galvanized steel protected edge

Fall Options: Available with built in fall, neutral or stepped fall

Locking System: CLIPFIX locking recess or STANDARD lock bar

Outlet: 4" bottom or end outlet connection

Load Class: A, B, C, E



Channel units with linear fall (0.5%)

| product description | length [inches] | total height [inches] | | product | #lbs/unit |
|---------------------|-----------------|-----------------------|-----|---------|-----------|
| | | start | end | | |
| J1001 | 39.4 | 5.9 | 6.1 | 155405 | 30.4 |
| J1002 | 39.4 | 6.1 | 6.3 | 155407 | 31.3 |
| J1003 | 39.4 | 6.3 | 6.5 | 155409 | 32.2 |
| J1004 | 39.4 | 6.5 | 6.7 | 155411 | 33.3 |
| J1005* | 39.4 | 6.7 | 6.9 | 155413 | 33.7 |
| J1006 | 39.4 | 6.9 | 7.1 | 155419 | 34.0 |
| J1007 | 39.4 | 7.1 | 7.3 | 155421 | 34.8 |
| J1008 | 39.4 | 7.3 | 7.5 | 155423 | 35.7 |
| J1009 | 39.4 | 7.5 | 7.7 | 155425 | 36.6 |
| J1010* | 39.4 | 7.7 | 7.9 | 155427 | 37.7 |
| J1011 | 39.4 | 7.9 | 8.1 | 155433 | 38.1 |
| J1012 | 39.4 | 8.1 | 8.3 | 155435 | 39.0 |
| J1013 | 39.4 | 8.3 | 8.5 | 155437 | 39.9 |
| J1014 | 39.4 | 8.5 | 8.7 | 155439 | 40.8 |
| J1015* | 39.4 | 8.7 | 8.9 | 155441 | 41.9 |
| J1016 | 39.4 | 8.9 | 9.1 | 155447 | 43.4 |
| J1017 | 39.4 | 9.1 | 9.2 | 155449 | 44.3 |
| J1018 | 39.4 | 9.2 | 9.5 | 155451 | 45.2 |
| J1019 | 39.4 | 9.5 | 9.7 | 155453 | 46.1 |
| J1020* | 39.4 | 9.7 | 9.8 | 155455 | 47.4 |

* With connection facility for vertical discharge outlet connector Ø 4" or silt box/gully

⚠ WARNING: Cancer and Reproductive Harm - www.p65warnings.ca.gov

Note

On request channel elements with total height of 9.9 to 12.0 inches are available. (J1021-J1030)

CLIPFIX: Recesses in channel edge accepts grate with pre-attached lock device to ensure positive locking of grate to channel. Removal of grate provides an unobstructed channel cross section for simple cleaning. Available on J1000 and S1000.

Applications

Public Areas

- Galvanized protected edge provides clean, uniform edge to finish
- Select heel-proof perforated or slotted grates

Warehouse facilities

- Protected edge prevents chipping abuse from forklift wheels
- Select ductile iron or reinforced slotted grates to withstand heavy loads