

MEADRAIN® Supreme



S1000

Clear Width: 4" interior
 Total Width: 5.1"
 Edge protection: Integrated stainless steel edge protection
 Fall Options: Available with built in fall, neutral or stepped fall
 Locking System: CLIPFIX or STANDARD
 Outlet: 4" bottom or end outlet
 Load Class: A, B, C, E



Channel units without fall

product description	length [inches]	total height [inches]	product #	lbs/ unit
S1000.0 ¹⁾	39.4	5.9	151601	29.8
S1000.1	19.7	5.9	151603	15.4
S1005.0 ¹⁾	39.4	6.9	151615	34.2
S1005.1 ¹⁾²⁾	19.7	6.9	151617	18.7
S1010.0 ¹⁾	39.4	7.9	151629	37.9
S1010.1 ¹⁾²⁾	19.7	7.9	151631	22.0
S1015.0 ¹⁾	39.4	8.9	151643	43.0
S1015.1 ¹⁾²⁾	19.7	8.9	151645	25.3
S1020.0 ¹⁾	39.4	9.8	151657	47.8
S1020.1 ¹⁾²⁾	19.7	9.8	151659	27.6

¹⁾ With connection facility for vertical discharge outlet connector Ø 4" or silt box/gully

²⁾ Connecting facility for corner and cross junction

Channel units for stepped fall

As connecting elements for stepped fall (with 2.5% fall).

product description	length [inches]	total height [inches]	product #	lbs/ unit	
		start	end		
S1000-5	39.4	5.9	6.9	151661	32.2
S1005-10	39.4	6.9	7.9	151663	35.9
S1010-15	39.4	7.9	8.9	151665	39.9
S1015-20	39.4	8.9	9.8	151667	45.5

⚠ WARNING: Cancer and Reproductive Harm - www.p65warnings.ca.gov

Note

For installation of stepped fall with neutral channels S1000.0 and S1005.0 connect with S1000-5. (S1021-S1030)
CLIPFIX: Recesses in channel edge accepts grate with pre-attached lock device to ensure positive locking of grate to channel. Removal of grate provides an unobstructed channel cross section for simple cleaning. Available on J1000 and S1000.

Applications

Commercial Kitchens

- Stainless Steel protected edge offers sanitary surface that is easy to clean
- Stainless Steel mesh grates for strong sanitary drainage surface

Bottling Areas

- Chemical Resistant edge to withstand frequent sanitizing
- Select perforated Stainless Steel gratings for non traffic areas and reinforced perforated for load bearing cart areas