

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---|---|--|--|---------------|---|--------|------------|-------|--|----|----------------------|--|-----|-------------------------------------|--|----|----------------------------|--|----|----------------|--|----|----------------------------|--|----|--------------------------|--|----|----------------------|--|
| 97-05-19 | <table border="1"> <thead> <tr> <th>ELKAY OPTIONS</th> <th>OPTION</th> <th>DEFINITION</th> <th>ELKAY</th> </tr> </thead> <tbody> <tr> <td rowspan="8"><u>OPTIONS THAT AFFECT CARRIER SELECTION ARE IN BOLD TYPE</u></td> <td>-C</td> <td>Complete with faucet</td> <td></td> </tr> <tr> <td>-CS</td> <td>Three faucet holes on 2 in. centers</td> <td></td> </tr> <tr> <td>-F</td> <td>Foot valve included</td> <td></td> </tr> <tr> <td>-G</td> <td>Specific color</td> <td></td> </tr> <tr> <td>-K</td> <td>Knee valve included</td> <td></td> </tr> <tr> <td>-L</td> <td>Faucet mounted on cooler</td> <td></td> </tr> <tr> <td>WO</td> <td>With Overflow device</td> <td></td> </tr> </tbody> </table> | | | | | ELKAY OPTIONS | OPTION | DEFINITION | ELKAY | <u>OPTIONS THAT AFFECT CARRIER SELECTION ARE IN BOLD TYPE</u> | -C | Complete with faucet | | -CS | Three faucet holes on 2 in. centers | | -F | Foot valve included | | -G | Specific color | | -K | Knee valve included | | -L | Faucet mounted on cooler | | WO | With Overflow device | |
| ELKAY OPTIONS | OPTION | DEFINITION | ELKAY | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <u>OPTIONS THAT AFFECT CARRIER SELECTION ARE IN BOLD TYPE</u> | -C | Complete with faucet | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | -CS | Three faucet holes on 2 in. centers | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | -F | Foot valve included | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | -G | Specific color | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | -K | Knee valve included | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | -L | Faucet mounted on cooler | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | WO | With Overflow device | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 99-07-01 | SINK | See Introduction about changes to rough in dimensions. | 17550 | 17550-M1557 | ELKAY | BE-50A | | | | | | | | | | | | | | | | | | | | | | | | |
| 01-10-02 | SINK | See Introduction about changes to rough in dimensions. | 17550 | 17550-M1581 | ELKAY | BE-50B | | | | | | | | | | | | | | | | | | | | | | | | | |
| 00-12-14 | SINK | B = 38-13/16 C = 18-1/4 J = 15 Δ = 31 See Introduction about changes to rough in dimensions. | 17560 | 17560 | ELKAY | CHS-1716 CHS-1716-C 16-3/4 X 15-1/2 | | | | | | | | | | | | | | | | | | | | | | | | | |
| 11-11-16 | LAVATORY | See Introduction about changes to rough in dimensions. | 17560 | 17560-M1675 | ELKAY | CHSB1716C CHSB17162 | | | | | | | | | | | | | | | | | | | | | | | | | |
| 05-06-24 | WATER COOLER | B = 33-7/16 C = 18-1/4 H = 20-11/16 J = 15 Δ = 33-5/8 See Introduction about changes to rough in dimensions. | 17560-WC 17550-WC | 17560-WC 17550-WC Use rows X & Z on hanger plate, row X on bearing plate. Mount both plates with half moon facing down. | ELKAY | EBFA-4 EBFA-8 EBFSA-4 EBFSA-8 | | | | | | | | | | | | | | | | | | | | | | | | | |

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| | TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|----------|----------------------------|---|---------------------------|--|---------------------------------|----------------------|
| 10-05-27 | FOUNTAIN | See Introduction about changes to rough in dimensions. | 17560 | 17560-M1654 | ELKAY | ECDFPW314C |
| 05-06-24 | DRINKING FOUNTAIN | B = 44-5/8 for -SP1T B = 44-1/16 for -008 C = 18-1/4 for -SP1T C = 15-3/4 for -008 H = 14-5/8 J = 12 Δ = 36 See Introduction about changes to rough in dimensions. | 17550-WC 17560-WC | 17550-WC-T 17560-WC-008 | ELKAY | EDF-10-C |
| 05-06-24 | DRINKING FOUNTAIN | B = 38-5/8 C = 18-1/4 H = 9-3/16 J = 12 Δ = 36 See Introduction about changes to rough in dimensions. | 17550-WC 17560-WC | 17550-WC 17560-WC | ELKAY | EDF-14-C |
| 05-06-24 | DRINKING FOUNTAIN | B = 58-1/8 C = 20-3/4 H = 20-11/16 J = 16-7/8 Δ = 40 See Introduction about changes to rough in dimensions. | 17560-WC | 17560-WC-017 | ELKAY | EDF-18-C |
| 05-06-24 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | 17720-66 17900 | 17720-66-66 17900-M1498 -M1498 is preferred | ELKAY | EDF-20-C |
| 97-10-21 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | | Manufacturer provides wall hanger which allows 1/4 in. or more between hanger and face of fountain for head of fastener. | ELKAY | EDFA-11-C |

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| | TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|----------|----------------------------|---|---------------------------|--|---------------------------------|----------------------|
| 02-04-25 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | | Manufacturer provides wall hanger which allows 1/4 in. or more between hanger and face of fountain for head of fastener. | ELKAY | EDFAC-211-C |
| 97-10-21 | DRINKING FOUNTAIN | Use Elkay MP-24 mounting box. See Introduction about changes to rough in dimensions. | | Use of carrier is not recommended. Mounting box is provided by manufacturer. | ELKAY | EDFB-12-C |
| 97-10-21 | DRINKING FOUNTAIN | Use two Elkay MP-24 mounting boxes. See Introduction about changes to rough in dimensions. | | Use of carrier is not recommended. Mounting box is provided by manufacturer. | ELKAY | EDFBC-212-C |
| 05-06-24 | DRINKING FOUNTAIN | B = 38-5/8 C = 18-1/4 H = 9-3/16 J = 12 Δ = 36 See Introduction about changes to rough in dimensions. | 17550-WC 17560-WC | 17550-WC 17560-WC | ELKAY | EDFP-10-C |
| 15-03-02 | DRINKING FOUNTAIN | B = 51-9/16 C = 18-1/4 H = 23-15/16 J = 11 Δ = 34-1/8 See Introduction about changes to rough in dimensions. | 17560-WC | 17560-WC | ELKAY | EDFP19C |
| 05-06-24 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | 17720-66 | 17720-66-66 This carrier is used to mount Elkay MP-86 mounting plate onto which the fountain is mounted. | ELKAY | EDFP-110-C |

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| | TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|----------|----------------------------|---|---------------------------|--|---------------------------------|--------------------------------------|
| 97-04-28 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | 17905 | 17905-M1436 | ELKAY | EDFP-117-C |
| 05-06-24 | DRINKING FOUNTAIN | B = 38-5/8 C = 18-1/4 H = 9-3/16 J = 12 Δ = 36 See Introduction about changes to rough in dimensions. | 17550-WC 17560-WC | 17550-WC 17560-WC | ELKAY | EDFP-14-C |
| 00-02-10 | DRINKING FOUNTAIN | B = 43 C = 36 C' = 20 J = 15-7/8 Δhigh = 39-7/8 to rim Δlow = 34 to rim See Introduction about changes to rough in dimensions. | 17905 | 17905-M1436 Lower three header rods provide support to the bottom of manufacturer's mounting plate and are not actually fastened to the mounting plate. | ELKAY | EDFP-17-C |
| 05-06-24 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | 17560-WC | 17560-WC | ELKAY | EDFP-210-C EDFP-214-C |
| 14-12-02 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | 17550 | 17550-WCBL-M1663 | ELKAY | EDFP217C EDFP217FPC EDFP217FPK |
| 19-02-08 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | 17560 | 17560-WCBL | ELKAY | EDFPBM117K EDFPBVM117FPK |

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| | TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|----------|----------------------------|--|---------------------------|---|---------------------------------|--------------------------|
| 05-06-24 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | 17720-66 | 17720-66-66 This carrier is used to mount Elkay MP-86 mounting plate onto which the fountain is mounted. | ELKAY | EDFPW-114-C |
| 12-06-18 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | 17560 | 17560-WCBL | ELKAY | EDFPVR217RC |
| 99-07-22 | DRINKING FOUNTAIN | B = 35-1/8 C = 24 H = 6-7/8 Δ = 33-3/4 to rim See Introduction about changes to rough in dimensions. | 17560 | 17560/1558 | ELKAY | EDFP-220-RC |
| 18-11-20 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | 17560 | 17560-WC | ELKAY | EDFPBWM114C |
| 02-05-30 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | 17550 | 17550-M1590 | ELKAY | EDFPAM117C EDFPBM117C |
| 02-05-30 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | 17720 | 17720-M1589 | ELKAY | EDFPW114C EDPPB114C |
| 05-06-24 | WATER COOLER | B = 51-1/2 C = 18-1/4 H = 6-15/16 J = 6 Δ = 34-3/4 See Introduction about changes to rough in dimensions. | 17560-WC | 17560-WC-R | ELKAY | EHFA-8 EHFSA-8 |
| 12-2-2 | FOUNTAIN | See Introduction about changes to rough in dimensions. | 17560 | 17560-WC | ELKAY | EHWM214C EHW214C |
| 1-23-18 | FOUNTAIN | See Introduction about changes to rough in dimensions. | 17560 | 17560-M1649 | ELKAY | EHW214FPK EHWM214FPK |

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| | TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|----------|-----------------|---|--|---|----------------------|--|
| 12-2-13 | FOUNTAIN | See Introduction about changes to rough in dimensions. | 17560 | 17560-WCBL | ELKAY | EHW217C EHW217C |
| 05-06-24 | WATER COOLER | B = 33-7/16 C = 18-1/4 H = 19-13/16 J = 15 Δ = 33-5/8 See Introduction about changes to rough in dimensions. | 17560-WC | 17560-WC | ELKAY | EIOA-4 EIOA-8 |
| 17-06-22 | LAVATORY | | 17720 | 17720-M1589 | ELKAY | ELV-1817 ELV-1817CS3 |
| 05-06-24 | LAVATORY | Use row X on SP1 plate with cutout up. | 17720-66 | 17720-66-M1561 | ELKAY | ELV-2219 WASH-UP 22 X 19 |
| 05-06-24 | LAVATORY | A = 29-3/4 B = 35-1/8 C = 18-1/4 for -SP1 C = 25 for -66 Y = 4 Δ = 31 Use rows W & X on top SP1 plate with cutout down. | 17550 17560 17590-DP 17720-66 | 17550 17560 17590-DP 17720-66-66 | ELKAY | ELV-2219 ELV-2219-CS ELVWO-2219 ELVWO-2219-CS WASH-UP 22 X 19 |
| 14-01-29 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560 | 17560-WC | ELKAY | EMABF8WS EMABF8WSSK EMABFDWS |
| 19-01-07 | WATER COOLER | B = 38-13/16" C = 18-1/4" C' = 18-1/4" D = 21-11/16" E = 32-5/16" F = 15-3/16" | 17560 | 17560-WCBL | ELKAY | EMABFTLR8 EMABFTLDDWSL K EMABFTLDDLC |
| 98-09-16 | WATER COOLER | See Introduction about changes to rough in dimensions. | | Use of carrier is not recommended. Mounting frame is provided by manufacturer. | ELKAY | ERP2-8-C |

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| | TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|----------|----------------------------|---|---------------------------|--|---------------------------------|---|
| 99-02-18 | WATER COOLER | See Introduction about changes to rough in dimensions. | | Use of carrier is not recommended. Mounting frame is provided by manufacturer. | ELKAY | ERFP-2-8 |
| 05-06-24 | LAVATORY | See Introduction about changes to rough in dimensions. | 17380-HD | 17380-HD-66 | ELKAY | ESLV-2820 SURGEON'S LAVATORY 22 X 19 |
| 05-06-24 | WATER COOLER | B = 59-9/16 C = 18-1/4 H = 22-3/16 J = 12-3/4 Δ = 40 See Introduction about changes to rough in dimensions. | 17560-WC | 17560-WC | ELKAY | ESRWC-8 70 lb shipping weight ESRWC-13 72 lb shipping weight |
| 18-05-11 | SINK | See Introduction about changes to rough in dimensions. | 17720-66 | 17720-66-M1765 | ELKAY | ESS-2520 ESSB-2520 ESSW-2520 SCRUB-UP 25 X 19-1/2 |
| 01-05-29 | SINK | See Introduction about changes to rough in dimensions. | 17720-66 | 17720-66-M1567 | ELKAY | ESS-4924-R ESS-4924-R-F-C SERVICE SINK 49 X 24 |
| 05-06-24 | WATER COOLER | B = 56-13/16 C = 18-1/4 H = 19-7/16 J = 12-3/4 Δ = 40 See Introduction about changes to rough in dimensions. | 17560-WC | 17560-WC-R | ELKAY | ESWA-8 ESWA-13 |

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| | TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|----------|----------------------------|---|---------------------------|----------------------|---------------------------------|---|
| 05-06-24 | WATER COOLER | B = 37-3/16 C = 18-1/4 $\Delta = 40$ See Introduction about changes to rough in dimensions. | 17550-WC 17560-WC | 17550-WC 17560-WC | ELKAY | EWA-4 EWA-8 EWA-14 EWA-16 EWA-20 |
| 05-06-24 | WATER COOLER | B = 37-3/16 C = 18-1/4 $\Delta = 40$ See Introduction about changes to rough in dimensions. | 17550-WC 17560-WC | 17550-WC 17560-WC | ELKAY | EWCA-4 EWCA-8 EWCA-14 |
| 05-06-24 | WATER COOLER | B = 37-3/16 C = 18-1/4 $\Delta = 40$ See Introduction about changes to rough in dimensions. | 17550-WC 17560-WC | 17550-WC 17560-WC | ELKAY | EWHA-8 EWHA-14 |
| | SINK | B = 46-11/16 C = 47 H = 20 J = 5-3/8 $\Delta = 36$ | 17720 | 17720-M1503 | ELKAY | EWMA-4820 MULTIPLE STATION 45 X 20 |
| | SINK | See Introduction about changes to rough in dimensions. | 17720 | 17720-M1449 | ELKAY | EWMA-6020 EWMA-6020C MULTIPLE STATION 57 X 20 |
| 14-01-14 | SINK | See Introduction about changes to rough in dimensions. | 17720 | 17720-M1716 | ELKAY | EWMA7220 EWMA7220C |
| 12-05-14 | SINK | See Introduction about changes to rough in dimensions. | 17720 | 17720-M1684 | ELKAY | EWMA9620C EWMA9620 EWMA96204 EWMA96208 |
| 03-05-23 | SINK | | 17720 | 17720-M1600 | ELKAY | EWSF13026 EWSF13026SACC |

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| | TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|----------|----------------------------|--|---------------------------|----------------------------|---------------------------------|---|
| 03-05-23 | SINK | | 17720-66 | 17720-66-M1601 | ELKAY | EWSF-26026 EWSF- 26026SACC |
| 02-02-12 | SINK | See Introduction about changes to rough in dimensions. | 17720-66 17720-66 | 17720-66 17720-66-M1562 | ELKAY | EWS2520 EWS2520FC SCRUB-UP 25 X 19-1/2 |
| 01-05-30 | SINK | See Introduction about changes to rough in dimensions. | 17720-66 | 17720-66-M1562 | ELKAY | EWS-2520-F-C SCRUB-UP 25 X 19-1/2 |
| 01-04-17 | SINK | See Introduction about changes to rough in dimensions. | 17720 | 17720-M1460 | ELKAY | EWS-2520-K-C SCRUB-UP 25 X 19-1/2 |
| 05-06-24 | SINK | A = 24-1/4 C = 17 Y = 5-3/8 Δ = 36 See Introduction about changes to rough in dimensions. | 17720-66 | 17720-66 | ELKAY | EWS-2520-W4-C EWS-2520-W6-C SCRUB-UP 25 X 19-1/2 |
| 02-02-12 | SINK | See Introduction about changes to rough in dimensions. | 17720-66 | 17720-66-M1587 | ELKAY | EWS3120 EWS3120FC SCRUB-UP 31 X 19-1/2 |
| 10-08-10 | LAVATORY | See Introduction about changes to rough in dimensions. | 17560 | 17560-M1659 | ELKAY | EWSFAD1362 |
| 12-03-16 | SINK | See Introduction about changes to rough in dimensions. | 17720 | 17720-M1684 | ELKAY | EWSFAD132620S ACC EWSFAD13620 |

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| | TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|----------|----------------------------|--|----------------------------------|--------------------------|---------------------------------|---|
| 05-06-24 | WATER COOLER | B = 37-1/8 C = 36 C' = 18 H = 29-5/8 Δ = 40 Δ = 32-1/2 See Introduction about changes to rough in dimensions. | 17550- WCBL | 17550-WCBL-013 | ELKAY | EWTLA-8 EWTLA-14 EWTLA-16 |
| 14-09-01 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | 17560 | 17560-WCBL | ELKAY | EZOSTL8C |
| 05-06-24 | WATER COOLER | B = 37-5/8 C = 36-1/2 C' = 18-1/4 D = 20 E = 32-1/8 F = 14-1/4 Δhigh = 36-13/16 Δlow = 31-5/16 See Introduction about changes to rough in dimensions. | 17560- WCBL 17550- WCBL | 17560-WCBL 17550-WCBL | ELKAY | EZSTL-8 EZTL-8 EZSTLDDC |
| 12-07-03 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | 17560 | 17560-WCBL | ELKAY | EZSTL8WSLK EZSTL8WSVRSK |
| 05-06-24 | WATER COOLER | B = 31-1/2 C = 18-1/4 H = 17-9/16 Δ = 31 5/16 See Introduction about changes to rough in dimensions. | 17560-WC | 17560-WC | ELKAY | EZ-4 EZS-4 EZ-8 EZS-8 EZS8GL EZS8L |
| 18-07-03 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560 | 17560-WC | ELKAY | EZS8S |
| 12-07-03 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560 | 17560-WC | ELKAY | EZS8WSLK EZS8WSSK |

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| | TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|----------|----------------------------|---|----------------------------------|---|---------------------------------|------------------------|
| 10-11-16 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560 | 17560-WCBL | ELKAY | EZSTL8C |
| 16-1-26 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560 | 17560-WCBL | ELKAY | EZSTLVR8 |
| 05-06-24 | WATER COOLER | B = 33-7/16 C = 18-1/4 H = 20-13/16 Δ = 35-3/8 to bubbler See Introduction about changes to rough in dimensions. | 17550-WC 17560-WC | 17550-WC * 17560-WC * Use row Z with plates mounted upside down. Use only row Z on bottom plate. | ELKAY | LIEA-8 LISEA-8 |
| 05-06-24 | WATER COOLER | B = 38-7/8 C = 36-1/2 C' = 18-1/4 D = 20-3/4 E = 33-1/2 F = 15-3/8 Δhigh = 40 3/4 to bubbler Δlow = 35-3/8 to bubbler Use rows X & Z on hanger plate, row X on bearing plate. Mount both plates with cutout down. See Introduction about changes to rough in dimensions. | 17560- WCBL 17550- WCBL | 17560-WCBL 17550-WCBL | ELKAY | LIEATL-8 |
| 97-07-16 | WATER COOLER | See Introduction about changes to rough in dimensions. | | Use of carrier is not recommended. Mounting frame is provided by manufacturer. | ELKAY | LKTE-8 |
| 15-3-23 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560-WC | 17560-WC | ELKAY | LMABF8WSLK |
| 17-04-17 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560- WCBL | 17550-WCBL | ELKAY | LMABFTL8 LMABFTL8WS |

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| | TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|----------|----------------------------|---|---------------------------|----------------------|---------------------------------|--|
| 13-11-20 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17550-WC | 17550-WC | ELKAY | LVRC8S |
| 18-3-29 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560-WC | 17560-WC | ELKAY | LVRC8WS LVRCDWS |
| 16-11-03 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560- WCBL | 17550-WCBL | ELKAY | LVRCGRNTL8WS K |
| 17-01-03 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560- WCBL | 17560-WCBL | ELKAY | LVRCTL8SC |
| 16-11-03 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560-WC | 17560-WC | ELKAY | LVRCGRN8WSK LVRCS8S3JO |
| 05-06-24 | WATER COOLER | B = 37-3/16 C = 18-1/4 $\Delta = 40$ See Introduction about changes to rough in dimensions. | 17550-WC | 17550-WC | ELKAY | LWCE-4 LWCE-8 |
| 18-03-13 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560-WC | 17560-WC | ELKAY | LZ08 LZOD |
| 05-06-24 | WATER COOLER | B = 29-9/16 C = 18-1/4 H = 15-5/8 $\Delta = 31-5/16$ See Introduction about changes to rough in dimensions. | 17560-WC | 17560-WC | ELKAY | LZ8 LZS8 |
| 17-11-07 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560 | 17560-WC | ELKAY | LZS8WSSP LZS8WSLK LZSDWSLK LZS8WSVRSK LZSDWSVRSK |

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| | TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|----------|----------------------------|--|----------------------------------|--|---------------------------------|---|
| 14-01-14 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560- WCBL | 17560-WCBL | ELKAY | LZTL-8 LZSTL8FC LZSTL8WSVRSK LZSTLDDWS LZSTLG8WS LZSTLG8WSSK |
| 05-06-24 | WATER COOLER | B = 38-13/16 C = 36-1/2 C' = 18-1/4 D = 21-13/16 E = 33-7/16 F = 16-7/16 Δhigh = 40 5/8 to bubbler Δlow = 35-3/8 to bubbler See Introduction about changes to rough in dimensions. | 17560- WCBL 17550- WCBL | 17560-WCBL 17550-WCBL | ELKAY | OBFATL-8-C |
| 05-06-24 | WATER COOLER | B = 33-7/16 C = 18-1/4 H = 20-11/16 J = 15 Δ = 33-5/8 See Introduction about changes to rough in dimensions. | 17560-WC 17550-WC | 17560-WC 17550-WC Use rows X & Z on hanger plate, row X on bearing plate. Mount both plates with half moon facing down. | ELKAY | OBF AVR-8 |
| 17-09-11 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560- WCBL | 17560-WCBL | ELKAY | PG8SBFSL PGSBFSL P8SBFSL |
| 12-2-10 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560 | 17560-WCBL | ELKAY | VRCGNTL8C |
| 13-06-06 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560 | 17560-WC | ELKAY | VRCGRN8 |
| 13-06-06 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560 | 17560-WC | ELKAY | VRCGRN8WSK |
| 11-02-15 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560 | 17560-WC | ELKAY | VRCHD8S |

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| | TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|----------|----------------------------|--|----------------------------------|-------------------------------------|---------------------------------|--|
| 12-08-17 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560 | 17560-WCBL | ELKAY | VRCTL8SC VRCTL8WSK VRCTLDDSC VRCTLDDSK VRCTLR8WSK VRCTLRDDWSK |
| 13-05-20 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560 | 17560-WC | ELKAY | VRC8S VRC8WSK VRCDS |
| 05-06-24 | LAVATORY | See Introduction about changes to rough in dimensions. | 17550-UR 17590-DP 17720-66 | 17550-UR 17590-DP 17720-66-66 | ELKAY | WCL-1923 WCL-1923-CS LUSTERTONE 23 X 19 |
| 18-01-02 | LAVATORY | See Introduction about changes to rough in dimensions. | 17720-66 | 17720-66-M1760 | ELKAY | WCL1923OSDC WCL1923OSD WCLWO1923OSDC WCLWO1923OSD |