

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

TYPE OF FIXTURE	ROUGH-IN DIMENSIONS	CARRIER SERIES	CARRIER MODEL	FIXTURE MANUFACTURER	FIXTURE MODEL												
96-05-13	<table border="1"> <tr> <td><b>PEERLESS OPTIONS</b></td> <td><b>OPTION</b></td> <td><b>DEFINITION</b></td> <td colspan="3"><b>PEERLESS</b></td> </tr> <tr> <td><b><u>OPTIONS THAT AFFECT CARRIER SELECTION ARE IN BOLD TYPE</u></b></td> <td><b>CAC</b></td> <td><b>Fixture is drilled for mounting on a concealed arm carrier</b></td> <td colspan="3"></td> </tr> </table>					<b>PEERLESS OPTIONS</b>	<b>OPTION</b>	<b>DEFINITION</b>	<b>PEERLESS</b>			<b><u>OPTIONS THAT AFFECT CARRIER SELECTION ARE IN BOLD TYPE</u></b>	<b>CAC</b>	<b>Fixture is drilled for mounting on a concealed arm carrier</b>			
<b>PEERLESS OPTIONS</b>	<b>OPTION</b>	<b>DEFINITION</b>	<b>PEERLESS</b>														
<b><u>OPTIONS THAT AFFECT CARRIER SELECTION ARE IN BOLD TYPE</u></b>	<b>CAC</b>	<b>Fixture is drilled for mounting on a concealed arm carrier</b>															
05-06-24 LAVATORY	A = 33 C = 16-3/4 F = 22-1/4 Δ = 34  <b>See Introduction about changes to rough in dimensions.</b>	17100-67 17100-BB-67 17125-67	17100-E30 17100-BB-E30 17125-AB-E30  The -E30 carrier arm assembly has all the same parts as the standard 17100-67 - 203 arm assembly plus a 1/4-20 X 3 in. long screw.	PEERLESS	45 46 ROOSEVELT 27 X 20 45 lb weight												
05-06-24 LAVATORY	<b>See Introduction about changes to rough in dimensions.</b>	17550-UR	17550-UR-SP1P	PEERLESS	65 66 LINCOLN 20 X 18 32 lb weight												
99-11-11 LAVATORY	A = 29-7/8 C = 16-3/4 F = 16-1/4 Δ = 31  <b>See Introduction about changes to rough in dimensions.</b>	17100 17125	17100-202P 17125-202-AD	* * PEERLESS	65CAC 66CAC LINCOLN 20 X 18 32 lb weight												
99-11-11 URINAL	B = 35-5/16 C = 18-1/4 E = 16-9/16 H = 16-9/16 J = 4 Δ = 24  <b>See Introduction about changes to rough in dimensions.</b>	17800 17810	17800SPM1559 17810SPM1559	PEERLESS	85 GIBSON 33 lb weight												