46600 (00-XY) SS Trench Channel 12" Wide

Specification

Josam series 46600 fabricated stainless steel (type 304, 2mm THK), 12" wide, v-shaped bottom, available with or without slope (1% STD.), with anchor tabs and leveling feet, no-hub bottom outlet and grate options. Run lengths longer than 13' provided with flanges and gaskets.

* 2" and 3" outlets use flat strainer.

Linear run

Total run length (L) =

* Start height (H1) (STD. 2-3/8" [60]) =

Height at outlet (H2) =

Or STD 1% slope

Outlet at end of run

Outlet mid-run (spec. LNGTH L1)


Non-linear run


Provide sketch with critical length and height dimensions and outlet location(s).

** When -FC is specified, start height (H1) is min. 4" [102]

OPTIONS:

-FB	Filter basket*
-SB	Sediment bucket (n/a 2",3")
-VP	Secured grate
-316	Type 316L material
-BW	Butt-weld outlet (spec. 10, 40, 80)
-T	Threaded outlet (2"-6")
-PFO	Push-Fit outlet diameter
-FC**	Flange and clamp
-OPH	Outlet plug with handle





X = Grate Type

0	No grate
1	Perforated sheet grate
2	Anti-slip mesh grate
3	Perimeter slot grate
4	Ladder grate

Y = Outlet DIA (Nom.)

2"
3"
4"
6"
8"

Josam product specifications in U.S. customary units are approximate and provided for reference only. For precise measurements, please contact Josam Technical Support. Josam reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Josam products previously or subsequently sold.

Notes:



T: (800) 365-6726 • Josam.com A **WATTS** Brand

ES-J-46600 2412 © 2024 Josam