

37900 SERIES

APPLICATION

For use in heavy traffic areas, such as packing houses or commercial parking decks for any type of floor construction where a medium to large flow of liquid is anticipated and a bucket is necessary to collect debris which may clog the waste line. LEVELEZE® adjustable collar permits accurate positioning of grate to meet finished floor level.

SPECIFICATION

JOSAM 37900 Series coated cast iron LEVELEZE® Floor Drain with square grate set in square secured frame, grate support collar with double drainage flange and weep-holes, bottom outlet, adjustable collar, support ring, large sump body, removable sediment bucket and heavy-duty ductile iron grate.

Available Options

<ul style="list-style-type: none"> -4 Secondary Flashing Clamp -15 Chained Grate -VP Secured Grate, Vandal-Proof Screws -19 Heavy-Duty Ductile Iron Undergrate w/Satin Finish Nikaloy Top -20 Heavy-Duty Ductile Iron Undergrate w/Satin Finish Bronze Top -70 Less Bucket -84 Stainless Steel Mesh Bucket Liner -88 Supplementary Strainer -92 Galvanized Cast Iron Parts 	<p>OUTLETS:</p> <ul style="list-style-type: none"> -T Threaded Outlet -X Inside Caulk Outlet -Y Hub Outlet, 2"-4" -Z No-Hub Outlet
---	---

14" PACKING HOUSE TYPE

37900 SLOT WIDTH 5/16"
37900-19 SLOT WIDTH 1/4"
37900-20 SLOT WIDTH 1/4"

CONFORMS WITH ASTM-C564.
THIS DIM. IS 5-3/4" ON 37908-T.
WITH -4 SECONDARY FLASHING CLAMP 2-1/4" MIN. 4-1/4" MAX.
ADD 1/4" WHEN FURNISHED WITH NIKALOY OR BRONZE TOP.

FOR OUTLET TYPE SPECIFY -T, -X, -Y or -Z			
TYPE NO.	PIPE SIZE	LBS.	
37902	2	82	
37903	3	82	
37904	4	81	
37905	5	81	
37906	6	80	
37908	8	80	

37960 SERIES

APPLICATION

For use in medium traffic areas, such as industrial plants or boiler rooms, for any type of floor construction where a square top complements construction or floor finish and a large sump is needed to handle a heavy flow of liquid. The secondary flat strainer protects the drain line from debris.

SPECIFICATION

JOSAM 37960 Series coated cast iron Floor Drain with double drainage flange, weepholes, bottom outlet, inside caulk connection, square top, square medium-duty, loose-set, SUPER-FLO® grate and secondary strainer.

Available Options

<ul style="list-style-type: none"> -1 Satin Finish Nikaloy Top -2 Satin Finish Bronze Top -7 Ductile Iron Grate -LG Less Grate, Cast Iron -LG-1 Less Grate, Nikaloy -LG-2 Less Grate, Bronze -11 Extra Heavy-Duty Grate -15 Chained Grate -LF Less Double Drainage Flange -C Bolted Flashing Clamp Device -49 3/4" Primer Tap -50 1/2" Primer Tap -81 Slotted Cast Iron Bucket -84 Stainless Steel Mesh Bucket Liner 	<ul style="list-style-type: none"> -92 Galvanized Cast Iron Parts -92-LF Galvanized Cast Iron Parts, Less Double Drainage Flange -92-LG-LF Galvanized Cast Iron Parts, Less Grate and Flange -ARE Acid-Resisting Epoxy (See 49400 Series) <p>OUTLET:</p> <ul style="list-style-type: none"> -X Inside Caulk Outlet
--	--

SUPER-FLO® 16" TOP

37960 SLOT WIDTH 9/16"
37960-1 SLOT WIDTH 1/2"
37960-2 SLOT WIDTH 1/2"

2" SIZE FURNISHED W/CAULK RING.
ADD 1/4" WHEN FURNISHED WITH NIKALOY OR BRONZE TOP.

FOR OUTLET TYPE SPECIFY -X					
TYPE NO.	PIPE SIZE	A	LBS.	LESS FLANGE	LBS.
37962	2▲	9-1/4	94	37962-LF	85
37963	3	9-1/4	96	37963-LF	86
37964	4	9-1/2	97	37964-LF	87
37965	5	9-7/8	98	37965-LF	88
37966	6	9-7/8	100	37966-LF	90