# Floor Drains

### **WEIGHT LOADS**

Apart from their primary purpose of receiving and conveying liquids, floor drains, as integral components of the floor, must be structurally suitable to withstand the anticipated loads that will be imposed on the floor. Weight support requirements of the drain vary with the location, construction, and service condition. The top loading classifications as published in Floor Drain Standard ANSI A112.21.1M-1980 are as follows:

> Light-Duty-All grates testing under 2000 lb. (900 kg.).

All grates testing between 2000 lb. (900 kg.) Medium-Duty-

and 4999 lb. (2250 kg.).

Heavy-Duty-All grates testing between 5000 lb. (2250 kg.)

and 7499 lb. (3375 kg.).


All grates testing between 7500 lb. (3375 kg.) Extra Heavy-Duty-

and 10,000 lb. (4500 kg.).


Special-Duty-Grates testing over 10,000 lb. (4500 kg.) should

be considered special and treated accordingly.


When the top loading requirements for a drain have been determined, the duty type needed can be resolved. Selection is easily accomplished as all JOSAM Floor Drains are classified according to duty type in this section. For specific detail loading data, contact JOSAM Engineering.








**HEAVY-DUTY GRATE** 



## -44 Option, Fixed Extension Collar




#### ORDERING INFORMATION

To specify or order a fixed extension collar with floor drain, add Option (-44) and height required to type number of drain.

Example: Type 32103 with a 6" extension would be designated: Type 32103 (-44)-6".

SERIES NO.	B In	D In	E In
32100, 32150, 32160	9-1/8	8-1/8	2
32200, 32300	12-5/8	11-3/4	2


## (-AE) Option, LEVELEZE® Adjustable Extension




The adjustable integral top is mated to the body and support ring with a heavy machined thread which permits virtually unlimited top level adjustment to accommodate various deck thicknesses. The line contact between the threads provides positive circumferential support of the top at any adjusted elevation.

## **Outlet Connections**

JOSAM drains are furnished with outlets for connection to most types of pipe. The timesaving, economical JIFFEE-JOINT Gasket is used for inside caulk connections (-X) to extra heavy or service weight soil pipe. No-hub spigot outlets (-Z) are also available for connection to no-hub soil pipe. The JIFFEE-SET Outlet (-Y) is for connecting hub outlet drains to PVC and ABS, service weight or no-hub soil pipe. Threaded outlets (-T) can be obtained on many series.







## (-66) OPTION

This option converts JOSAM bottom outlet inside caulk drains to no-hub side outlet drains using a 90° no-hub quarter bend and a JIFFEE-JOINT Gasket.

PIPE SIZE	A	В	С
2	2-1/2	4-1/2	3-5/8
3	2-13/16	5	4-1/2
4	3-1/2	5-1/2	5-11/16
5	4-5/16	6-1/2	6-15/16
6	4-13/16	7	7-15/16








Floor Drains 123


grate, allowing it to intercept debris entering the interior of the drain. This option is

primarily used in drains which don't offer a sediment bucket.







30000-WF6S Series SUPER-FLO® Adjustable Strainer Floor Drain shown installed in a composition deck floor. Wide flange assures that bonding of floor material is watertight and permanent.




32100-81 Series SUPER-FLO® Floor Drain shown installed in a mediumduty single-pour concrete floor supported by steel construction.

124 Floor Drains







32100-AE-81 Series SUPER-FLO® Floor Drain shown installed in a poured concrete floor with floor finish. LEVELEZE® Adjustable Collar provides vertical adjustment, facilitating installation and forming a perfect surface between top of drain and floor finish.





39600 Series Planting Area Drain shown in a typical installation providing drainage for an indoor planting area. Stainless mesh screen covered dome prevents entrance of dirt and gravel at the base of the planting area.


Floor Drains 125
































Floor Drains

SATIN FINISH BRONZE

CAST IRON

DATE OF LAST CHANGE. PLANTERS

DIMENSIONS ARE SUBJECT TO MANUFACTURERS

TOLERANCES AND CHANGE WITHOUT NOTICE.


WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA.

-93

DATE OF LAST CHANGE:


GALVANIZED CAST IRON


F8





**JOSAM COMPANY** 


MICHIGAN CITY, INDIANA







































#### SPECIFICATION: FLOOR DRAIN JOSAM SERIES 30000-ST COATED CAST IRON FLOOR DRAIN, WITH SHALLOW TRAP TWO-PIECE BODY WITH DOUBLE DRAINAGE FLANGE, 1/2" PRIMER TAP WITH PLUG, WEJLOC INVERTIBLE CLAMP COLLAR THREADED FOR JOSAM ADJUSTABLE STRAINERS WITH SIDE OUTLET SHALLOW TRAP. 30000-ST **SERIES** \* THREADED TRAP OUTLET STD. NO-HUB TRAP OUTLET AVAIL. (-Z) SIZE 6 3/4" -IPS PRIMER TAP 1/2" W/ PLUG (STD.) 3/4" (USE -49 OPT.) PIPE SIZE NPT THREADED-CONNECTION 2" TRAP SEAL PIPE SIZE MODEL В OPTIONS 30002-ST 2-1/2" 7-1/2" ACID-RESISTING EPOXY 30002-ST-Z 8" 2 2-1/2" 3/4" PRIMER TAP 30003-ST 2-1/4" 9-7/8" GALVANIZED CAST IRON PARTS -92 30003-ST-Z 2-1/4" 10-1/4" NO-HUB SIDE OUTLET TRAP DATE OF LAST CHANGE: **JOSAM COMPANY** DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCES AND CHANGE WITHOUT NOTICE. WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA.


MICHIGAN CITY, INDIANA





















FLOOR DRAIN


SPECIFICATION:

























#### SPECIFICATION: FLOOR DRAIN JOSAM 30000-M SERIES CAST IRON FLOOR DRAIN, TWO-PIECE BODY WITH DOUBLE DRAINAGE FLANGE AND 1/2" PRIMER TAP, ADJUSTABLE FLOOR DRAIN WEJLOC® INVERTIBLE FLASHING COLLAR, WEEPHOLES, BOTTOM OUTLET CONNECTION AND CHROME PLATED 30000-M ADJUSTABLE STANDPIPE WITH DOME SERIES GASKET ON -Y CONNECTION CONFORMS WITH ASTM-C564 ADJUSTABLE STRAINER 6" STANDARD, FOR OTHER W/ STANDPIPE & DOME HEIGHT SPECIFY ON ORDER FLASHING COLLAR X MIN Y MAX 1/8) \$3 3/4-PS PRIMER TAP 1/2" w/ PLUG (STD.) 3/4" (USE -49 OPT.) PIPE SIZE 3" STRAINER Х 4" 2 1/8 1/2 1 7/8 -TSO THREADED SIDE OUTLET BRONZE ADJUSTABLE STRAINER WITH SHALLOW TRAP (2" AND 3" ONLY) LESS DOME -PD PRISON DRAIN (2" AND 3" ONLY) -PF PERFORATED STANDPIPE -ARE ACID-RESISTING EPOXY THREADED OUTLET 3/4" PRIMER TAP INSIDE CAULK OUTLET -91 ROUGH BRONZE BODY HUB OUTLET WITH GASKET ● GALVANIZED CAST IRON PARTS NO-HUB SPIGOT OUTLET RAWING No. 06/18/08 NOTES: JOSAM COMPANY A-15603-K MICHIGAN CITY, INDIANA














FLOOR DRAIN

SHALLOW TRAP, ADJUSTABLE STRAINER

X MIN. Y MAX.

30000-ST-A

PIPE SIZE

STAINLESS STEEL STRAINER PARTS

PERF. STAINLESS STEEL BASKET

CHROME PLATED STRNR (5A.6A)

GALVANIZED CAST IRON PARTS

NOTES


NO-HUB SIDE OUTLET TRAP


ACID-RESISTING EPOXY


3/4" PRIMER TAP


SATIN FIN. BRONZE STRAINER PARTS


SECURED GRATE, VANDAL-PROOF SCREWS

























#### SPECIFICATION: FLOOR DRAIN JOSAM 32100 SERIES COATED CAST IRON FLOOR DRAIN, TWO-PIECE BODY WITH DOUBLE DRAINAGE FLANGE, WEJLOC © NON-9" ROUND TOP, SUPER-FLO® PUNCTURING FLASHING COLLAR, WEEPHOLES, BOTTOM OUTLET, ROUND TOP, MEDIUM-DUTY LOOSE-SET ANTI-TILTING SUPER-FLO® GRATE WITH PERIMETER DRAINAGE SLOTS 32100 **SERIES** GRATE FREE AREA: 27 IN2 SLOT WIDTH 3/8" Ø 12 5/8" ( -1 & -2 SLOT WIDTH 3/16" **♦ GASKET CONFORMS WITH** ASTM-C564 \*ADD 1/4" WHEN FURNISHED WITH NIKALOY OR BRONZE TOP = 4-3/4"\* -X = 6-1/2"\*♦-Y = 5-7/8" $-Z = 5-3/4"^*$ -Z OUTLET SHOWN SIZE → PIPE SIZE SOLID CAST IRON COVER SECURED GRATE, VANDAL-PROOF SCREWS PIPE SIZE ACID-RESISTING EPOXY LEVELEZE @ ADJUSTABLE EXTENSION FIXED EXTENSION COLLAR, CAST IRON ( SPEC, HT. ) 3" STD. SLOTTED CAST IRON BUCKET FIXED EXTENSION COLLAR, GALVANIZED ( SPEC. HT. ) 3" STD. TRACTOR GRATE 3/4" PRIMER TAR LOCKING COVER, SATIN FINISH NIKALOY 1/2" PRIMER TAP LOCKING COVER, SATIN FINISH BRONZE STAINLESS STEEL MESH BUCKET LINER SATIN FINISH NIKALOY TOP SUPPLEMENTARY STRAINER SATIN FINISH BRONZE TOP GALVANIZED CAST IRON PARTS DUCTILE IRON GRATE -66 NO-HUB SIDE OUTLET EXTRA-HEAVY DUTY GRATE, CAST IRON HEEL-PROOF GRATE, CI, 5/16" SLOT WIDTH, 25 SQ IN FREE AREA DOME GRATE, CAST IRON THREADED OUTLET DOME GRATE, NIKALOY INSIDE CAULK OUTLET HUB OUTLET WITH GASKET DOME GRATE, BRONZE CHAINED GRATE NO-HUB OUTLET DATE OF LAST CHANGE: NOTES JOSAM COMPANY IMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCES AND CHANGE WITHOUT NOTICE WE CAN ASSUME NO RESPONSIBILITY FOR MICHIGAN CITY, INDIANA USE OF SUPERSEDED OR VOID DATA.







FLOOR DRAIN

SPECIFICATION:


#### SPECIFICATION:


JOSAM 32100-AE-81 SERIES COATED CAST IRON LEVELEZE FLOOR DRAIN, TWO PIECE BODY WITH DOUBLE DRAINAGE FLANGE, WEJLOC NON-PUNCTURING FLASHING COLLAR, WEEPHOLES, BOTTOM OUTLET, ADJUSTABLE COLLAR WITH ROLLED THREAD AND ROUND TOP WITH REMOVABLE SEDIMENT BUCKET THAT SUPPORTS A MEDIUM-DUTY LOOSE-SET ANTI-TILTING SUPER-FLO GRATE WITH PERIMETER DRAINAGE SLOTS

#### FLOOR DRAIN

9" ROUND TOP LEVELEZE®, SUPER-FLO®

32100-AE-81 SERIES





#### OPTIONS

X	-AE	LEVELEZE ADJUSTABLE EXTENSION	-50	1/2" PRIMER TAP
Х	-81	SLOTTED CAST IRON BUCKET	-66	NO-HUB SIDE OUTLET
	-1	SATIN FINISH NIKALOY TOP	-84	STAINLESS STEEL MESH BUCKET LINER
	-2	SATIN FINISH BRONZE TOP	-88	SUPPLEMENTARY STRAINER
	-7	DUCTILE IRON GRATE	-92	GALVANIZED CAST IRON PARTS
	-15	CHAINED GRATE	-T	THREADED OUTLET
	-VP	SECURED GRATE, VP SCREWS	-X	INSIDE CAULK OUTLET
	-ARE	ACID-RESISTING EPOXY COATING	-Y	HUB OUTLET WITH GASKET
	-49	3/4" PRIMER TAP	-Z	NO-HUB OUTLET

DATE OF LAST CHANGE:	04/25/15
DIMENSIONS ARE SUBJECT TO M TOLERANCES AND CHANGE WIT	
WE CAN ASSUME NO RESPON	ISIBILITY FOR
USE OF SUPERSEDED OR \	OID DATA.

JOSAM COMPANY MICHIGAN CITY, INDIANA

NOTES

#### SPECIFICATION:


USE OF SUPERSEDED OR VOID DATA.

JOSAM 32100-AE-LC1-88 SERIES COATED CAST IRON FLOOR DRAIN, TWO-PIECE BODY WITH DOUBLE DRAINAGE FLANGE, WEJLOC® NON-PUNCTURING FLASHING COLLAR, WEEPHOLES, BOTTOM OUTLET, ROUND SATIN NIKALOY HINGED KEY-LOCKING COVER, ADJUSTABLE COLLAR AND INTERNAL STRAINER


#### FLOOR DRAIN


9" ROUND TOP, LOCKING COVER

SERIES 32100-AE-LC1-88




MICHIGAN CITY, INDIANA








FLOOR DRAIN

SPECIFICATION:









FLOOR DRAIN

SPECIFICATION:

