

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|-----------------|---------------------|----------------|---------------|----------------------|---------------|
|-----------------|---------------------|----------------|---------------|----------------------|---------------|

98-03-19

| OASIS OPTIONS | OPTION | DEFINITION | OASIS |
|---|-------------|---------------------------------------|-------|
| <p><u>OPTIONS THAT AFFECT CARRIER SELECTION ARE IN BOLD TYPE</u></p> <p>OEP units have been replaced by (and are essentially the same as) PLF units. PLF stands for <u>pressure lead free</u>.</p> | -AE | Cooler has a timed push pad | |
| | -D | specific type of control valve switch | |
| | -E | specific type of control valve switch | |
| | DP | specific type of control valve switch | |
| | -EE | Same as PLF | |
| | ODP | Electric eye controlled valve | |
| | -Q | Electric eye controlled valve | |
| | -SL | Same as PLF | |
| | -V | Cooler has four push pads. | |
| | | Split Level cooler or fountain | |
| | Versacooler | | |

| | | | | | | |
|----------|-------------------|---|-------|-------------|-------|----------|
| 96-04-18 | DRINKING FOUNTAIN | B = 39-1/8 C = 15-1/4 Δ = 40 to bottom of bubbler | 17895 | 17895-M1508 | OASIS | FLF110PM |
|----------|-------------------|---|-------|-------------|-------|----------|

See Introduction about changes to rough in dimensions.

| | | | | | | |
|----------|-------------------|--|----------|-------------------|-------|--------|
| 05-06-24 | DRINKING FOUNTAIN | B = 62-1/2 C = 18-1/4 H = 26-1/8 J = 15-5/16 Δ = 40 to rim | 17560-WC | 17560-WC-SP1 * | OASIS | FLF130 |
|----------|-------------------|--|----------|-------------------|-------|--------|

Use row Z on top plate with cutouts up on both plates.

See Introduction about changes to rough in dimensions.

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| | TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|----------|----------------------------|--|---------------------------|--|---------------------------------|----------------------|
| 18-12-13 | DRINKING FOUNTAIN | B = 62-1/2 C = 18-1/4 H = 28-5/8 J = 15-5/16 Δ = 40 to rim Use row Z on top plate with cutouts up on both plates. See Introduction about changes to rough in dimensions. | 17560-WC | 17560-WC-SP1 * | OASIS | FLF201PM |
| 97-04-02 | DRINKING FOUNTAIN | B = 33-3/16 C = 15-1/4 Δ = 36 to bubbler See Introduction about changes to rough in dimensions. | 17895 | 17895-M1508 | OASIS | FLF140PM |
| 97-08-26 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | | Use of carrier is not recommended. Mounting frame is provided by manufacturer. | OASIS | FLF231PM |
| 12-03-28 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560-WC | 17560-WC-SP1U | OASIS | M140RFZ |
| 00-04-12 | WATER COOLER | See Introduction about changes to rough in dimensions. | | Use of carrier is not recommended. Mounting frame is provided by manufacturer. | OASIS | M8SCEE M8SCPM |

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| | TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|----------|-------------------|--|----------------------|--|----------------------|----------------------------|
| 97-06-30 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | | Use of carrier is not recommended. Mounting frame is provided by manufacturer. | OASIS | MSSLPM |
| 17-07-06 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560-WCBL | 17560-WCBL | OASIS | PGF8EBFSL PG8FEBFSL |
| 20-01-21 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | 17560-WC | 17560-WC | OASIS | PG8SBF |
| 18-10-22 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | 17560-WCBL | 17560-WCBL | OASIS | PG8ACSL |
| 05-06-24 | WATER COOLER | <p>$B = 37-13/16$</p> <p>$C = 18-1/4$</p> <p>$H = 11-7/8$</p> <p>$J = 12-1/4$</p> <p>$\Delta = 40$ to rim</p> <p>Use rows X and Z on top plate, row X on bottom plate.</p> <p>See Introduction about changes to rough in dimensions.</p> | 17550-WC 17560-WC | 17550-WC-SP1 * 17560-WC-SP1 * | OASIS | PLF1CM PLF3CM PLF5CM |
| 05-06-24 | WATER COOLER | <p>$B = 38$</p> <p>$C = 18-1/4$</p> <p>$H = 22-9/16$</p> <p>$J = 7-1/8$</p> <p>$\Delta = 40$ to rim</p> <p>See Introduction about changes to rough in dimensions.</p> | 17550-WC 17560-WC | 17550-WC-SP1 * 17560-WC-SP1 * | OASIS | PLF8SM |

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| | TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|----------|-------------------|---|----------------------|---|----------------------|----------------------|
| 05-06-24 | DRINKING FOUNTAIN | See Introduction about changes to rough in dimensions. | 17550-WC 17560-WC | 17550-WC-SP1 * 17560-WC-SP1 * | OASIS | PLFCM |
| 05-06-24 | WATER COOLER | B = 33-1/2 C = 18-1/4 H = 19-1/8 Δ = 34-1/2 to bubbler See Introduction about changes to rough in dimensions. | 17550-WC 17560-WC | 17550-WC-SP1 17560-WC-SP1 Mount top plate cut out down. | OASIS | P8AM P8SBF PAM |
| 05-06-24 | WATER COOLER | B = 32 C = 18-1/4 H = 15-3/8 Δ = 33 to bubbler See Introduction about changes to rough in dimensions. | 17550-WC 17560-WC | 17550-WC-SP1 17560-WC-SP1 Mount top plate cut out down. | OASIS | P8AC PAC |
| 05-06-24 | WATER COOLER | B = 37 C = 18-1/4 C' = 36-1/2 E = 31 Δ = 37 1/32 Δ = 31 1/32 See Introduction about changes to rough in dimensions. | 17550-WCBL | 17550-WCBL-SP1 Mount Plates with cut-out's down. | OASIS | PACSL |

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|-----------------------|--|--------------------------|----------------------------------|----------------------|--|
| 05-06-24 WATER COOLER | <p>$B = 40-5/8$ $C = 36-1/2$ $C' = 18-1/4$</p> <p>$D = 27-3/16$</p> <p>$E = 33-1/8$</p> <p>$F = 19-11/16$</p> <p>$\Delta_{high} = 40$ to rim $\Delta_{low} = 32-1/2$ to rim</p> <p>See Introduction about changes to rough in dimensions.</p> | 17560-WCBL 17550-WCBL | 17560-WCBL-SP1 17550-WCBL-SP1 | OASIS | P8AMSL P8AMSLEE AQUARIUS 98 lb net weight |
| 05-06-24 WATER COOLER | <p>$B = 32-5/8$ $C = 18-1/4$ $H = 16-23/32$ $J = 15$ $\Delta = 36$</p> <p>See Introduction about changes to rough in dimensions.</p> | 17550-WC 17560-WC | 17550-WC-SP1U 17560-WC-SP1U | OASIS | PLF8M |
| 96-05-08 WATER COOLER | <p>$B = 37-15/16$ $C = 34$ $C' = 17$ $D = 24$ $E = 32-1/16$ $F = 18-1/8$ $\Delta_{high} = 40$ $\Delta_{low} = 34-1/8$</p> <p>See Introduction about changes to rough in dimensions.</p> | 17905 17910 | 17905-M1493 17910-M1493 | OASIS | PLF8WMQSL |

CARRIER SELECTION AND FIXTURE ROUGHING-IN DIMENSIONS

| | TYPE OF FIXTURE | ROUGH-IN DIMENSIONS | CARRIER SERIES | CARRIER MODEL | FIXTURE MANUFACTURER | FIXTURE MODEL |
|----------|-----------------|---|----------------------|--------------------------------|----------------------|--|
| 05-06-24 | WATER COOLER | B = 50 C = 18-1/4 H = 22-9/16 J = 14-5/16 Δ = 35-3/4 See Introduction about changes to rough in dimensions. | 17550-WC 17560-WC | 17550-WC-SP1S 17560-WC-SP1S | OASIS | PLF8SKPE PLF8SKTP |
| 05-06-24 | WATER COOLER | B = 32-5/8 C = 18-1/4 H = 16-23/32 J = 15 Δ = 36 to bubbler See Introduction about changes to rough in dimensions. | 17550-WC 17560-WC | 17550-WC-SP1U 17560-WC-SP1U | OASIS | PSF8WMQ |
| 12-07-17 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17550-WC | 17550-WC | OASIS | PG8AC PGAC PGF8AC PGFAC |
| 13-07-30 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560 | 17560-WCBL-M1709 | OASIS | P8ACSL P8ACSLEE PF8ACSLEE PF8ACSL PVF8ACSL PGV8ACSL |
| 13-12-10 | WATER COOLER | See Introduction about changes to rough in dimensions. | 17560 | 17560-WC-M1714 | OASIS | PGVAC PGVAC-14G PGV8AC PGV8AC-14G |